


4051


LUMINÁRIA SUSPENSA



DESENHO TÉCNICO . TECHNICAL DRAWING . DISEÑO TÉCNICO . DESSIN TECHNIQUE .



FOTOMETRIA . PHOTOMETRY . FOTOMETRÍA . PHOTOMÉTRIE .



CODE	LAMP	L (mm)
4051.114.xDL	T5 14W	600
4051.121.xDL	T5 21W	900
4051.128.xDL	T5 28W	1200
4051.135.xDL	T5 35W	1500
4051.124.xDL	T5 24W	600
4051.139.xDL	T5 39W	900
4051.149.xDL	T5 49W	1500
4051.154.xDL	T5 54W	1200
4051.180.xDL	T5 80W	1500

Luminária em alumínio extrudido. Difusor em policarbonato ou micro prismático.

Luminaire in extruded aluminium. Polycarbonate or micro prismatic diffuser.

Luminaria en aluminio extruido. Difusor en policarbonato o micro prismático.

Luminaire en aluminium extrudé. Diffuseur en polycarbonate ou micro-prismatique.



DRIVER 220-240VAC-50/60Hz · 50 000 @L80, B10, TA 25°C
CRI>80 · UGR <19

Normas: EN 60598-1, EN 60598-2-1

CORES E ACABAMENTOS . COLORS AND FINISHES . COLORES Y ACABADOS . COULEURS ET FINITIONS .

- 1 Branco
White . Blanco . Blanc .
- 3 Cinza Satinado
Satin Gray . Gris Satinado . Gris Satin .
- 4 Escovado
Brushed . Cepillado . Brossé .
- Grafite
Graphite . Grafite . Graphite .
- 9 Preto
Black . Negro . Noir .
- 0 RAL sob consulta
RAL on request . RAL bajo consulta . RAL sur demande .
- O Opalino
Opaline . Opalino . Opal .
- P Micro prismático
Micro prismatic . Micro prismático . Microprismatique .

1-10V code:
0Y00.000.0XX > Y+1

DALI code:
0Y00.000.0XX > Y+2

Pode ser instalado em linhas contínuas, com o comprimento pedido. Outras medidas sob consulta.
Can be installed in continuous lines, with the requested length. Other measures available under consultation.
Puede ser instalado en líneas continuas, con la longitud solicitada. Otros comprimentos bajo pedido.
Peut être installé en lignes continues, avec la longueur demandée. Des autres mesures disponibles sur demande.